(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 15 January 2004 (15.01.2004)

PCT

(10) International Publication Number WO 2004/006365 A1

(51) International Patent Classification7: 4/88, 8/02

H01M 4/86,

(21) International Application Number:

PCT/NL2003/000492

(22) International Filing Date:

3 July 2003 (03.07.2003)

(25) Filing Language:

Dutch

(26) Publication Language:

English

(30) Priority Data: 1020985

3 July 2002 (03.07.2002)


- (71) Applicant (for all designated States except US): STICHT-ING ENERGIEONDERZOEK CENTRUM NEDER-LAND [NL/NL]; Westerduinweg 3, NL-1755 LE Petten (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): NAMMENSMA, Pieter [NL/NL]; Saturnuslaan 36, NL-1702 BC Heerhugowaard (NL). DE ROOY, Robert [NL/NL]; Montgomerystraat 11, NL-1931 VW Egmond aan Zee (NL).

BROERSEN, Bartholomeus, Cornelis [NL/NL]; Jan Arentsweg 14, NL-1749 HP Warmenhuizen (NL).

- (74) Agent: VAN WESTENBRUGGE, Andries; Nederlandsch Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: ANODE-SUPPORTED FUEL CELL



(57) Abstract: Anode-supported fuel cell, in particular SOFC, where stresses in the anode substrate are compensated for by a stress compensation layer. According to the invention said stress compensation layer is made porous by making a large number of vary small openings. These openings are preferably made hexagonal and the thickness of the walls between the openings is minor. An electron-conducting porous layer is applied to the stress compensation layer.